High Flow Extinguishers

7595 GADSDEN HWY. ❖ TRUSSVILLE, ALABAMA 35173 ❖ PH: (205) 655-3271 ❖ FAX: 1-800-654-5980 ❖ email:sales@amerex-fire.com

Amerex is now producing High Flow portable fire extinguishers for applications where discharge rates exceeding one pound per second are required as specified in NFPA 10. These extinguishers utilize the same hardware and are manufactured to the same U.L. specifications as Amerex compliance rated products. The High Flow extinguishers have a 6 year warranty.

FEATURES:

Same hardware and valve components as our standard models

Twice the flow rate of standard models

Chrome plated brass valve

Stainless steel handle and lever

Large loop stainless steel pull pin with lanyard

Meets DOT requirements

UL listed, 10 and 20 lb. sizes

USCG Approved

ABC, Regular, PK Dry Chemical Choices

SPECIFICATIONS						
Model Number	720	760	721	761	722	762
Agent	ABC	ABC	REGULAR	REGULAR	PURPLE K	PURPLE K
Capacity (lbs.)	10	20	10	20	10	20
Application	HOSE & NOZZLE		HOSE & NOZZLE		HOSE & NOZZLE	
U/L Rating	1A:20B:C	4A:60B:C	20B:C	60B:C	20B:C	60B:C
Shipping Weight (lbs.)	19	39	19	39	19	39
Discharge Time (sec.)	10	19	10	20	11	20
Discharge Rate (lbs./sec.)	1.22	1.14	1.15	1.13	1.15	1.08
Discharge Range (ft.)	15-25	15-25	15-25	15-25	15-25	15-25
Height (in.)	20½	24	20½	24	20½	24
Width (in.)	8¾	10¼	8¾	10¼	8¾	10¼
Depth (in.)	5	7	5	7	5	7
Temperature Range (°F)	-65°F to 120°F					
Bracket Type	WALL		WALL		WALL	

MADE IN U.S.A.!

© 2011 Amerex Corporation